




the pressure equipment safety authority

STATUTORY DECLARATION  
Registration of Fittings



"See Acceptance Letter for the comments and/or conditions of registration"

I, Amy Wang,  
Manager  
(company title, e.g. vice president, plant manager, chief engineer) (must be in a position of authority)  
of Shurjoint Metals Inc.  
(name of manufacturer)

located at No. 295, Sec. 3 Wandan Road, Wandan Township, Pingtung, Taiwan R.O.C  
(plant address)

do solemnly declare that the fittings listed hereunder, which are subject to the Safety Codes Act (check one)

- comply with the requirements of ASME B 31.3 which specifies the dimensions, (title of recognized North American Standard) materials of construction, pressure/temperature ratings and identification marking of the fittings, or
- are not covered by the provisions of a recognized North American standard and are therefore manufactured to comply with \_\_\_\_\_ as supported by the attached data which identifies the dimensions, materials of construction, pressure/temperature ratings and the basis for such ratings, and the marking of the fittings for identification.

I further declare that the manufacture of these fittings is controlled by a quality control program which has been verified by the following authority, LRQA certificate No. TWN0955771 as being suitable for the manufacture of these fittings to the stated standard. The fittings covered by this declaration, for which I seek registration, are category A

In support of this application, the following information, calculations and/or test data are attached:  
See attachment 1

DECLARED before me at Kaohsiung in the Republic of China

this 3rd day of JUN, 2016  
(Month) (Year)

(print) HUANG, CHI-RONG

(sign) Huang, Chi-Rong  
(A Commissioner for Oaths)

[Signature]  
(Signature of Applicant)

For Office Use Only TN 2016-03886

To the best of my knowledge and belief, the application meets the requirements of the Safety Codes Act and CSA Standard B51, Clause 4.2, and is accepted for registration in Category A

Registration Number: 0A01966.72

Date Registered: MAR 31 2017

[Signature]  
(For the Administrator/Chief Inspector of Alberta)  
Expiry Date: Jun 24 2026

The information you provide is necessary only for the administration of the programs as required by the Alberta Safety Codes Act and Regulations in the Boiler Discipline

Complete acceptance letter for this fitting registration must be provided to the end user/owner. UR

"See Acceptance Letter for the comments and/or conditions of registration"

# CRN Registration

May 13, 2016

Shurjoint Grooved Components are to be registered.

Fittings:

Copper Series Products

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawing
C305	2", 2-1/2", 3", 4", 5", 6"	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-C305 H1C7 GC4 7705TB
C306	2-1/2"x2", 3"x2", 3"x2-1/2", 4"x2-1/2", 4"x3", 5"x4", 6"x4"	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-C306 H1CD GCD 7705TB
C307	2", 2-1/2", 3", 4"	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-C307 H1C9 GC9 7705TB
C10	2", 2-1/2", 3", 4", 5", 6"	225	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1CSDa
C11	2", 2-1/2", 3", 4", 5", 6"	175	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	
C20	2", 2-1/2", 3", 4", 5"	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	
	6"	150		
C60	2", 2-1/2", 3", 4", 5", 6"	175	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1C6

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawing
C21	2-1/2"x2", 3"x2", 3"x2-1/2", 4"x2", 4"x2-1/2", 4"x3", 5"x3", 5"x4", 6"x2-1/2", 6"x3", 6"x4", 6"x5"	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1CRDa
C50	2-1/2"x2", 3"x2", 3"x2-1/2", 4"x2", 4"x2-1/2", 4"x3", 5"x3", 5"x4", 6"x2-1/2", 6"x3", 6"x4", 6"x5"	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	
C26	2"x3/4", 2"x1", 2"x1-1/4", 2"x1-1/2", 2-1/2"x3/4", 2-1/2"x1", 2-1/2"x1-1/4", 2-1/2"x1-1/2", 2-1/2"x2", 3"x3/4", 3"x1", 3"x1-1/4", 3"x1-1/2", 3"x2", 4"x3/4", 4"x1", 4"x1-1/4", 4"x1-1/2", 4"x2"	175	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1CG
C52	2"x1", 2"x1-1/4", 2"x1-1/2", 2-1/2"x1", 2-1/2"x1-1/4", 2-1/2"x1-1/2", 2-1/2"x2", 3"x1-1/2", 3"x2", 4"x2"	175	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1C7
C55	1-1/2"x2", 2"x2", 2-1/2"x2-1/2", 3"x3"	175	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1CC
DE30-GG	2", 2-1/2", 3", 4", 5", 6"	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	132

# CRN Registration

May 13, 2016

Shurjoint Grooved Components are to be registered.

Fittings:

Stainless Steel Series Products

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawing
SS-7	1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"	250	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1S7 G15a STB
SS-7X	10", 12", 14", 16", 18", 20", 22", 24"	150	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SS7X H1SUa H1SUb G15a G15b STB
SS-8	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	As-SS8 H1S8 G15a STB
SS-8X	3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SS8X H18X G15a STB
SS-10	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	SSD
SS-11	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	
SS-20	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawing
SS-60	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1S4
SS-21	1-1/4"x1", 1-1/2"x1", 1-1/2"x1-1/4", 2"x1", 2"x1-1/4", 2"x1-1/2", 3"x2-1/2", 4"x2-1/2", 4"x3", 5"x4", 6"x3"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1SRDa
SS-50	1-1/4"x1", 1-1/2"x1", 1-1/2"x1-1/4", 2"x1", 2"x1-1/4", 2"x1-1/2", 2-1/2"x1", 2-1/2"x1-1/4", 2-1/2"x1-1/2", 2-1/2"x2", 3"x1-1/4", 3"x1-1/2", 3"x2", 3"x2-1/2", 4"x2", 4"x2-1/2", 6"x4", 8"x4", 8"x6"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	
SS-21F	2-1/2"x2", 3"x2", 4"x2"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1S6
SS-50F	2-1/2"x2", 3"x2", 4"x2"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	1S5
SS-723	1-1/4"x1/2", 1-1/4"x3/4", 1-1/4"x1", 1-1/2"x1/2", 1-1/2"x3/4", 1-1/2"x1", 2"x1/2", 2"x3/4", 2"x1"	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SS723 1SHU 1SHL G133b STB