UNIFORM STATUTORY DECLARATION FORM FOR THE REGISTRATION OF FITTING DESIGNS

NEW BRUNSWICK NUNAVUT	NOVA SCOTIA YUKON	PRINCE EDWARD ISLAND NORTHWEST TERRITORIES	NEWFOUNDLAND AND LABRADOR		
MANUFACTURERS NAM	E: Aalberts integrated pipin	g systems APAC Inc.			
MANUFACTURERS ADD	RESS: No. 295, Sec. 3, Wandan	Road, Wandan Township, Pingtung, Taiwa	n R.O.C.		
PLANT LOCATIONS:	As above				
CATEGORY OF	FITTINGS TO BE REGISTERED	. CIRCLE ONE CATEGORY ONLY	TITLE OF THE STANDARD OF CONSTRUCTION		
B Flanges: all flanges C Valves: all line valves	couplings, tees, elbows, Ys, plugs,		ASME B31.3		
F Measuring devices, inci- pressure transmitters	uding pressure gauges, level gau	ges, sight glasses, levels, or e as primary over pressure protection on			
boilers, pressure vesse	is, piping and fusible plugs		en (station)		
Control Contro	ponents that do not fall into one of	the above categories (Meeting CNSC or ASME requirements)	and the second s		
		SO AS IT WILL APPEAR ON THE PRODUC	TYPE OF CONSTRUCTION		
<u>a</u>	and/or SH	FORGED CI WELDED CI WROUGHT D			
my knowledge represent temperature ratings, and manufacture of these fitt or in part and has been v	lity of the end product do sole is the product for which registr I identification markings are in ings is regulated by a Quality yarified by LRQA certificate No. Is	mnly declare that the information containation is sought. The dimensions, mater accordance with the herein named star	ndards. I further declare that the plant where fabrication occurs in whole that purpose and I make this solemn		
, ,	CHIU, YING CH		enect as it made brider basi.		
Signature of Declarer:		10///			
Declared before me at	Katholung .	**************************************	S SPACE FO		
This > 6 day of Commissioner of Ouths or Notary Public: (sign)	TELL AD)-Thay	FICIAL OFA ₁		
or Notal y Physics, (algrey)	This registration must be reva	space for Regulatory Authority use alidated after ten (10) years from the dal	te of acceptation reliand		
CRN: 0B1967.7	Rev2	ė.	Service NL		
FID#: 16031		27	2010111-110		
	d company name change from 8		2 /10 /18		
to Aalberts Integrated Pil forcepper tubing; SS FI	oing Systems APAC Inc. CDI F g. adapters; SS & CDI Univ. flg.	lg. adapter adapters;	Engineering and Inspection Services		
	istered in the name of the Manufa a supported with two Statutory De		Registered by		
forms and one copy of su	pporting documentation.		UNDER THE AUTHORITY OF THE		
The declaration shall to responsibility for the qual	se made by the person having full	authority and	PUBLIC SAFETY ACT AND		
	ns shall be resubmitted for valida	tion	THE BOILER, PRESSURE SSEL AND		
at a maximum interval of			COMPRESSED CAS RECULATIONS		
	five (5) years. 0; CDI fig. adapters; CDI Univ. r	educing fig. adapters.	Sect. 1.0 - Fittings Rev. 1.0		

CRN Registration

Shurjoint Grooved Components are to be registered (Category B - Flanges)

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawings
7170 Flange Adapter	2~8	300	$-20^{\circ}\text{F} \sim +180^{\circ}\text{F}$ $(-29^{\circ}\text{C} \sim +82^{\circ}\text{C})$	170
7180 Universal Flange Adapter	2 ~ 8	300	-20°F ~ +180°F (-29°C ~ +82°C)	180
7181 Universal Reducing Flange Adapter	3 x 2, 4 x 2½, 4 x 3, 6 x 4	125	-20°F ~ +180°F (-29°C ~ +82°C)	1AG
7041	2 ~ 6	300	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	HA104a
Flange Adapter	10 ~ 12	175		
7043 Flange Adapter - ANSI Class 300	2, 21/2, 3, 4, 5, 6, 8, 10, 12	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-7043 H143 G14a 7041HB
SS-41 Flange Adapter	2, 2½, 3, 4, 6, 8	175	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SS41 H1SG G14a 7041HB
SS-80 Stainless Steel Universal Flange Adapter	2, 21/2, 3, 4, 5, 6, 8	250	-20°F ~ +180°F (-29°C ~ +82°C)	189
C341 Flange for Copper Tubing	2, 21/2, 3, 4, 5, 6	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-C341 1C5 GC5 7041HB