

345 Carlingview Drive Toronto, Ontario M9W 6N9 Tel.: 416.734.3300 Fax: 416.231.1626 Toll Free: 1.877.682.8772

www.tssa.org

June 29, 2021

MISTER CRN CONSULTING INC. PO BOX 488 MONTAGUE PE C0A 1R0

Workorder Type: Registration - Fitting(Conventional)

Workorder No: SR3019836 Your Reference No.: LOG 2769

Registered to: AALBERTS INTEGRATED PIPING SYSTEM APAC INC.

Dear MILLER WEST,

Technical Standards and Safety Authority (TSSA) is pleased to inform you that your submission has been reviewed and registered as follows:

CRN: 0B1967.75R2

Main Design No.: 0B1967.75R1 RENEWAL AND COMPANY NAME CHANGE

Expiry Date: Dec 18, 2030

Please be advised that a valid quality control system must be maintained for the fitting registration to remain valid until the expiry date.

R2: CRN RENEWAL AND COMPANY NAME CHANGE

The stamped copy of the approved registration and the invoice are mailed separately (There will be no hard copies for electronic submissions). Should you have any questions or require further assistance, please contact a Customer Service Advisor at 1.877.682.TSSA (8772) or e-mail customerservices@tssa.org. We will be happy to assist you. When contacting TSSA regarding this file, please refer to the Service Request number provided above.

Yours truly,

Norman Ngan

Norman Ngai P. Eng. Mechanical Engineer

Engineer, BPV

Tel.: +1 416-734-3557 Email: NNgai@tssa.org

CRN Registration

Shurjoint Grooved Components are to be registered (Category B - Flanges)

| Model Number | Size Range (inch) | Rated Pressure (psi) | Service Temperature | Drawings |
|--|--------------------------------|----------------------------|---|-----------------------------------|
| 7170 Flange Adapter | 2~8 | 300 | $-20^{\circ}\text{F} \sim +180^{\circ}\text{F}$ $(-29^{\circ}\text{C} \sim +82^{\circ}\text{C})$ | 170 |
| 7180 Universal Flange Adapter | 2 ~ 8 | 300 | -20°F ~ +180°F (-29°C ~ +82°C) | 180 |
| 7181 Universal Reducing Flange Adapter | 3 x 2, 4 x 2½, 4 x 3, 6 x 4 | 125 | -20°F ~ +180°F (-29°C ~ +82°C) | 1AG |
| 7041 Flange Adapter | 2 ~ 6 | 300 | EPDM: -20°F ~ +180°F (-29°C ~ +82°C) | HA104a |
| | 10 ~ 12 | 175 | | |
| 7043 Flange Adapter - ANSI Class 300 | 2, 21/2, 3, 4, 5, 6, 8, 10, 12 | 200 | EPDM: -20°F ~ +180°F (-29°C ~ +82°C) | AS-7043 H143 G14a 7041HB |
| SS-41 Flange Adapter | 2, 2½, 3, 4, 6, 8 | 175 | EPDM: -20°F ~ +180°F (-29°C ~ +82°C) | AS-SS41 H1SG G14a 7041HB |
| SS-80 Stainless Steel Universal Flange Adapter | 2, 21/2, 3, 4, 5, 6, 8 | 250 | -20°F ~ +180°F (-29°C ~ +82°C) | 189 |
| C341 Flange for Copper Tubing | 2, 21/2, 3, 4, 5, 6 | 200 | EPDM: -20°F ~ +180°F (-29°C ~ +82°C) | AS-C341 1C5 GC5 7041HB |