

April 29, 2021

Attention: Miller West MISTER CRN CONSULTING INC BOX 488 MONTAGUE, PE C0A 1R0

The design submission, tracking number 2021-00325, originally received on January 21, 2021 was surveyed and accepted for registration as follows:

CRN : 0C01968.72

Accepted on: April 29, 2021

Reg Type:RENEWALExpiryDrawing No. : TABLE 1; SCOPE OF FITTING DESIGNES (CATEGORY C)

Expiry Date: December 18, 2030

Fitting type: VALVES

Design registered in the name of : AALBERTS INTEGRATED PIPING SYSTEMS APAC INC

The registration is conditional on your compliance with the following notes:

As indicated on AB-41 Statutory Declaration form and submitted documentation, the code of construction is ASME B31.3.

- It is our understanding that the fitting(s), included as the scope of this submission, that is(are) subject to the Safety Codes Act shall comply with the requirements of the indicated Standard or Code of Construction on the AB-41 Statutory Declaration as supported by the attached data which identifies the dimensions, materials of construction, press./temp. ratings and the basis for such ratings, and the identification marking of the fittings.

- This registration is valid only for fittings fabricated at the location(s) covered by the QC certificate attached to the accepted AB-41 Statutory Declaration form.

- This registration is valid only until the indicated expiry date and only if the Manufacturer maintains a valid quality management system approved by an acceptable third-party agency until that date.

- Should the approval of the quality management system lapse before the expiry date indicated above, this registration shall become void.

An invoice covering survey and registration fees will be forwarded from our Revenue Accounts.

If you have any question don't hesitate to contact me by phone at (780) 433-0281 ext 3382 or fax (780) 437-7787 or e-mail Stojanovic@absa.ca.

Sincerely,

STOJANOVIC, STEVAN, P. Eng. DOP Cert. No. D00008849

CRN Registration

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawings
SJ-C300 Butterfly Valve for Copper Tubing	2, 21/2, 3, 4, 5, 6	150	EPDM: -4°F ~ +230°F (-20°C ~ +110°C)	AS-SJC300 1CKa 1CKb 1CKc
SJ-600 Ball Valve	11/2, 2, 21/2, 3, 4	300	-20°F ~ +230°F (-7 °C ~ +110°C)	AS-SJ600SS-a AS-SJ600SS-b 1SXa 1SXb 1SXc 1SXc 1SXd 1SXd
SJ-400 Butterfly Valve	3, 4	250	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ400 1CNa 1CNb 1CNc
SJ-300N Butterfly Valve	2, 21/2, 3, 4	300	EPDM: -4°F ~ +230°F (-20°C ~ +110°C)	AS-SJ300N 1J3a 1J3b 1J3c
RCV Riser Check Valve	21/2, 3, 4, 5, 6	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-RCV 1RVa 1RVb
	8	125		1RVc 1RVd 1RVe 1RVf
SJ-200 Low Profile Butterfly Valve	2, 21/2, 3, 4, 6	125	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ200 1JNa 1JNb 1JNc 1JNd

Shurjoint Grooved Components are to be registered (Category C -Valves)

Model Number	Size Range (inch)	Rated Pressure (psi)	Service Temperature	Drawings
SJ-300F Resilient Seated Butterfly Valve	21/2, 3, 4, 5, 6	200	EPDM: -20°F + +180°F (-29°C ~ +82°C)	AS-SJ300F AS-SJ300F-a 1JLa 1JLb 1JLc 1JLd 1JLd 1JLe 1JLf 1JLi
SJ-500L Ball Valve	11/2, 2, 21/2, 3	250	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	
	4, 6	200		SJ500-C-3
SJ-900 Swing Check Valve	21/2, 3, 4, 5, 6	200	EPDM: -20°F ~ +180°F	AS-SJ900 1J9a 1RVb 1RVc
	8	150	(-29°C ~ +82°C)	1RVd 1RVe 1RVf
SJ-930 Horizontal Swing Check Valve	2, 21/2, 3, 4	200	EPDM: -20°F ~ +180°F (-29°C ~ +82°C)	AS-SJ930 1AJa 1AJb 1AJc AS-7771 H108a AS-XH70EP H1X8 G15a 7705TB 160a S819001
SJ-915 Dual Disc Check Valve	21/2, 3, 4, 6, 8	300	EPDM: -20°F ~ +180°F	AS-SJ915 AS-SJ915_b
	10, 12	150		1JKa 1JKb
	14, 16, 18, 20, 24	100	(-29°C ~ +82°C)	1JKc 1JKd 1JKe