

Model SJ-300FV

File Number: EX15439

COMPANY

Aalberts integrated piping systems APAC Inc
295 SEC 3 WANDAN RD
WANDAN TOWNSHIP
PINGTUNG HSIEN, 913 Taiwan

MODEL INFO

SJ-300FV
Butterfly Valve

ATTRIBUTES AND RATINGS				
Size, NPS	End Configuration	Pressure Rating, psig (kPa)	Indicator Post	Supervisory Tamper Switch
2, 76.1 mm, 2-1/2, 3, 4, 5, 139.7 mm, 6, 165.1 mm	Groove	300 (2068)	No	Indoor installation, Outdoor installation
8, 216.3 mm, 10, 267.4 mm	Groove	300 (2068)	No	Indoor installation, Outdoor installation
12, 318.4 mm	Groove	300 (2068)	No	Indoor installation, Outdoor installation



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."