

VIZA.EX4689 - Fittings, Grooved and Plain End

Fittings, Grooved and Plain End

Aalberts integrated piping systems APAC Inc

295 SEC 3 WANDAN RD
WANDAN TOWNSHIP
PINGTUNG HSIEN, 913 Taiwan

EX4689

The following fittings are intended for use with Aalberts integrated piping systems APAC Inc (EX4688) Listed rubber gasketed fittings.

| Model | Type | Size In. | Rated Pressure (psig) |
|--------|---------------------|--|-----------------------|
| 899 | Grooved by Female | 1-1/4 x 1/2, 3/4, 1; | 300 |
| | NPT 90 degree elbow | 1-1/2 x 1/2, 3/4, 1; | |
| | | 2 x 1/2, 3/4, 1; | |
| | | 2-1/2 x 1/2, 3/4, 1 | |
| 901 | 90 Degree Elbow | 2, 2-1/2, 3, 4, 5, 6, 8; | 300 |
| | (Short Radius) | 3.0 OD, 6.5 OD | |
| 903 | Tee | 2, 2-1/2, 3, 4, 5, 6, 8; | 300 |
| | (Short Radius) | 3.0 OD, 6.5 OD | |
| 7110 | 90 Degree Elbow | 20, 24 | 250 |
| | | 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12, 14, 16, 18 | 300 |
| | | 76.1 mm, 139.7 mm, 165.1 mm, 216.3 mm, 267.4 mm, 318.5 mm | |
| 7110DR | Drain Elbow | 2, 2-1/2, 3, 4, 6 | 300 |
| 7110LR | Elbow(Long Radius) | 2, 2-1/2, 3, 4, 6, 8 | 300 |
| 7111 | 45 Degree Elbow | 20, 24 | 250 |
| | | 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12, 14, 16, 18 | 300 |
| | | 76.1 mm, 139.7 mm, 165.1 mm, 216.3 mm, 267.4 mm, 318.5 mm | |
| 7112 | 22-1/2 Elbow | 1-1/2 | 500 |
| | | 2, 2-1/2, 3.0 OD, 3, 4, 5, 6, 6.5 OD, 8 | 300 |
| 7113 | 11-1/4 Elbow | 2, 2-1/2, 3.0 OD, 3, 4, 5, 6, 6.5 OD, 8 | 300 |
| 7120 | Tee | 20, 24 | 250 |
| | | | |

| | | | |
|-------|---------------------------------------|---|-----|
| | | 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12, 14, 16, 18 | 300 |
| | | 76.1 mm, 139.7 mm, 165.1 mm, 216.3 mm, 267.4 mm, 318.5 mm | |
| 7121 | Reducing Tee | 2 x 1-1/2; | 300 |
| | | 2-1/2 x 2; | |
| | | 3 x 2, 2-1/2; | |
| | | 4 x 2, 2-1/2, 3; | |
| | | 6 x 2, 2-1/2, 3, 4; | |
| | | 8 x 2, 3, 4, 6; | |
| | | 10 x 4, 6, 8; | |
| | | 12 x 3, 4, 6, 8, 10 | |
| 7125 | Bullhead Tee | 2 x 2-1/2; | 300 |
| | | 2-1/2 x 3, 4; | |
| | | 4 x 6; | |
| | | 5 x 8; | |
| | | 6 x 8 | |
| 7127 | Standpipe Tee | 4 x 2-1/2; | 300 |
| | | 6 x 2-1/2 | |
| 7130 | 45 Lateral | 2, 2-1/2, 3, 3.0 OD, 4, 5, 6, 6.5 OD, 8 | 300 |
| 7135 | Cross | 2, 2-1/2, 3, 4, 5, 6, 8 | 300 |
| 7150 | Concentric Reducer (Groove Type A) | 4 x 2, 2-1/2, 3; | 300 |
| | | 6 x 2, 2-1/2, 3, 4 | |
| | (Groove Type B) | 2 x 1-1/2; | |
| | | 8 x 3, 4, 6; | |
| | | 10 x 4, 6, 8; | |
| | | 12 x 8, 10; | |
| | | 14 x 8, 10, 12; | |
| | | 16 x 8, 10, 12, 14; | |
| | | 18 x 12, 14, 16 | |
| | (Groove Type C) | 2-1/2 x 2; | |
| | | 3 x 2, 2-1/2 | |
| | (Groove Type B) | 20 x 16, 18; | 250 |
| | | 24 x 12, 14, 16, 18, 20 | |
| 7150F | Reducing Socket | 1-1/2 x 1; | 300 |

| | | | |
|----------|--------------------------------------|---|-----|
| | Adapter | 2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2, 2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/2, 2, 2-1/2; 5 x 1-1/2; 6 x 1-1/2, 2, 2-1/2, 4 | |
| 7150M | Reducing Nipple | 1-1/2 x 1; 2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2, 2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/2, 2, 2-1/2; 5 x 1-1/2; 6 x 1-1/2, 2, 2-1/2, 4 | 300 |
| 7151 | Eccentric Reducer (Groove Type A) | 6 x 2 | 300 |
| | (Groove Type B) | 2-1/2 x 2; | |
| | | 3 x 2, 2-1/2; | |
| | | 4 x 2, 2-1/2, 3; | |
| | | 6 x 3, 4; | |
| 8 x 4, 6 | | | |
| 7160H | Cap | 10, 12, 14, 16, 18 | 300 |
| | | 20, 24 | 250 |
| 7160 | Cap | 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10 | 300 |
| | | 12 | 175 |
| | | 2 x 1, 1-1/4; | 300 |
| | | 2-1/2 x 1, 1-1/4, 1-1/2; | |
| | | 3 x 1, 1-1/4, 1-1/2, 2; | |
| | | 4 x 1, 1-1/4, 1-1/2, 2; | |
| | | 6 x 1, 1-1/4, 1-1/2, 2; | |
| | | 76.1 mm, 139.7 mm, 165.1 mm, 216.3 mm, 267.4 mm | 300 |
| 318.5 mm | 175 | | |
| 7170 | Flange Adapter | 2-1/2, 3, 4, 5, 6 | 175 |
| 7180 | Flange Adapter | 2, 2-1/2, 3, 4, 5, 6, 8 | 300 |
| 55 | Nipple Adapter | 1-1/2, 2 | 300 |

| | | | |
|--------|------------------------|---|-----|
| 850 | Sprinkler Hub | 2 x 1 (3 outlets); 2-1/2 x 1 (3 outlets); 76.1 mm x 1 (3 outlets) | 300 |
| 851 | Reducing Sprinkler Hub | 2 x 1-1/2 x 1 (3 outlets); 2-1/2 x 1-1/2 x 1 (3 outlets); 2-1/2 x 2 x 1 (3 outlets); 76.1 mm x 2 x 1 (3 outlets) | 300 |
| 853 | Sprinkler Hub | 1-1/2 x 1 (4 outlets); 2 x 1 (4 outlets); 2-1/2 x 1 (4 outlets); 76.1 mm x 1 (4 outlets) | 300 |
| SS-10 | 90 Elbow | 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8 | 300 |
| SS-11 | 45 Elbow | 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8 | 300 |
| SS-20 | Tee | 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8 | 300 |
| SS-21 | Tee | 3 x 2-1/2; | 300 |
| | | 4 x 2-1/2 | |
| SS-21F | Tee | 3 x 2; | 300 |
| | | 4 x 2 | |
| SS-50 | Tee | 3 x 2-1/2; | 300 |
| | | 4 x 2-1/2 | |
| SS-50F | Concentric Reducer | 2-1/2 x 2; | 300 |
| | | 3 x 2; | |
| | | 4 x 2 | |
| SS-60 | Cap | 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8 | 300 |
| SS-80 | Flange Adapter | 2, 2-1/2, 3, 4, 5, 6, 8 | 300 |
| C10 | 90 Elbow | 2, 2-1/2, 3, 4 | 175 |
| C11 | 45 Elbow | 2, 2-1/2, 3, 4 | 175 |
| C20 | Tee | 2, 2-1/2, 3, 4, 6 | 175 |
| C21 | Reducing Tee | 2-1/2 x 2; | 200 |
| | | 3 x 2, 2-1/2; | |
| | | 4 x 2, 2-1/2, 3; | |
| | | 5 x 3, 4; | |
| | | 6 x 2-1/2, 3, 4, 5 | |
| C26 | Reducing Tee | 2 x 3/4, 1, 1-1/4, 1-1/2; | 200 |
| | | 2-1/2 x 3/4, 1, 1-1/4, 1-1/2; | |
| | | 3 x 3/4, 1, 1-1/4, 1-1/2; | |
| | | 4 x 3/4, 1, 1-1/4, 1-1/2 | |

| | | | |
|-----|--------------------|-----------------------------|-----|
| C50 | Concentric Reducer | 2-1/2 x 2; | 200 |
| | | 3 x 2, 2-1/2; | |
| | | 4 x 2, 2-1/2, 3; | |
| | | 5 x 3, 4; | |
| | | 6 x 2-1/2, 3, 4, 5 | |
| C52 | Concentric Reducer | 2 x 1, 1-1/4, 1-1/2; | 200 |
| | | 2-1/2 x 1, 1-1/4, 1-1/2, 2; | |
| | | 3 x 1-1/2, 2; | |
| | | 4 x 2 | |
| C60 | Cap | 2, 2-1/2, 3, 4 | 200 |

Trademark and/or Tradename:  **SHURJOINT**, "SJ", "SHURJOINT"

Last Updated on 2021-10-18

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"