



VIZU.EX6981 - Fittings, Welded Outlet

Fittings, Welded Outlet

[See General Information for Fittings, Welded Outlet](#)

AALBERTS INTEGRATED PIPING SYSTEMS APAC INC

EX6981

295 SEC 3 WANDAN RD
 WANDAN TOWNSHIP
 PINGTUNG HSIEN, 913 TAIWAN

Model	Outlet Pipe Size, in.	Run Pipe Size, in.	Pipe	Rated Pressure, psig
71	1/2, 1	1-1/4	10, 40	300
71	1/2, 1	1-1/2	10, 40	300
71	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	2	10, 40	300
71	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	2-1/2	10, 40	300
71	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	3	10, 40	300
71	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	4	10, 40	300
71	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	5	10, 40	300
71	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	6	10, 40	300
71	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	8	10, 40	300
72C	2	2	10, 40	300
72C	2, 2-1/2	2-1/2	10, 40	300
72C	2, 3	3	10, 40	300
72C	2, 2-1/2, 3, 4	4	10, 40	300
72C	2, 2-1/2, 3, 4	5	10, 40	300
72C	2, 2-1/2, 3, 4, 6	6	10, 40	300
72C	2, 2-1/2, 3, 4, 6, 8	8	10, 40	300
72C	8	10	10, 40	300
72R	1-1/4	1-1/4	10, 40	300
72R	1-1/4, 1-1/2	1-1/2	10, 40	300
72R	1-1/4, 1-1/2, 2	2	10, 40	300
72R	1-1/4, 1-1/2, 2, 2-1/2	2-1/2	10, 40	300
72R	1-1/4, 1-1/2, 2, 2-1/2, 3, 2-1/2 (76.1 mm OD)	3	10, 40	300

72R	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 2-1/2 (76.1 mm OD)	4	10, 40	300
72R	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 2-1/2 (76.1 mm OD)	5	10, 40	300
72R	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 2-1/2 (76.1 mm OD)	6	10, 40	300
72R	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 2-1/2 (76.1 mm OD)	8	10, 40	300
74	1-1/4 through 8	1/2	10, 40	300
74	1-1/4 through 8	3/4	10, 40	300
74	1-1/4 through 8	1	10, 40	300

Trademark and/or Tradename:  **SHURJOINT** , "SJ", "SHURJOINT"

Last Updated on 2020-12-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"